



PSG30 | PSG50 Stacked Washer-Extractor/ Tumble Dryer



SAFETECH FIRE SUPPRESSION SYSTEM
For maximal safety of your operations



SENSO DRY+ TECHNOLOGY
Lower energy and utility costs, lower linen replacement costs



CLOUD - BASED PLATFORM
to easily monitor your laundry everywhere and at any time



RADIAL AND AXIAL AIRFLOW
For maximal heat transfer, low energy consumption and short drying time



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a 3-year warranty

FEATURES & BENEFITS

Features

- Ideal for limited space settings
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

Maximize Time and Space

PRIMUS stacked washer-extractor/ tumble dryer is a unique product that truly delivers increased productivity. Featuring the Xtronic Touch Control.



PLATFORM: XCONTROL FLEX

- Available with XControl FLEX
- 7" (5" on stack tumbler dryers), full color, touch screen display
- Clear step-by-step instructions available in 34 languages
- Machine programming & performance data accessible through cloud. Remotely access to live machine data on mobile device
- VEND:
 - » 5 standard dry programmes (High, Medium, Low, Delicate, No Heat)
 - » 15 easy-to-use washer cycle modifier
- Count up timer
- Over-the-air updates

Stacked Washer-Extractor/Tumble Dryer

Specifications

		PSG30		PSG50		
		Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer	
Control Option		XControl FLEX		XControl FLEX		
Capacity - lb (kg)		30 (13.6) x 2		50 (23) x 2		
Overall Width - in (mm)		31.4 (797)		34.4 (875)		
Overall Depth - in (mm)		45.5 (1152)		51.3(1302)		
Overall Height - in (mm)		79.7 (2023)		84.3(2141)		
Cylinder Diameter - in (mm)		24.0(610)	30.0 (762)	26.3 (668)	33.0 (838)	
Cylinder Depth - in (mm)		16.0 (406)	26.0 (660)	20.3(515)	30.0 (762)	
Cylinder Volume - cu. ft (liters)		4.2 (119)	10.6 (300)	6.3(178)	14.8(419)	
Reversing Cylinder		-	Standard	-	Standard	
Door Opening Size - in (mm)		14.3(363)	22.6(574)	16.3(414)	26.9 (683)	
Door Bottom to Floor - in (mm)		14.0(356)	51.3(1303)	14.6 (370)	52.3 (1328)	
Water Inlet Connection - in (mm)		2 x 0.75 (19)	-	2 x 0.75 (19)	-	
Drain Diameter - in (mm)		1 x 3 (76)	-	1 x 3 (76)	-	
Drain Height to Floor - in (mm)		4.3 (108)	-	4.5 (115)	-	
Heat Input Power - Btu/hr (kW, Mj/hr.)		- 73,000 (21.4, 77.0)		-	95,000 (27.8, 100)	
Gas Connection - in		-	1/2 NPT	-	1/2 NPT	
Air Outlet - in (mm)		-	8.0 (200) Elliptical	-	10.0 (250) Elliptical	
Airflow - cfm (l/sec)		-	400 (190)	-	600 (285)	
Motor - HP (kW)	Fan	-	0.5 (0.4)	-	0.5 (0.4)	
	Drive	1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)	
Total # of Speeds		9	-	9	-	
Cylinder Speeds - RPM (G-Force)	Gentle	34 (0.4)	-	33 (0.4)	-	
	Wash	48 (0.8)	-	46 (0.8)	-	
	Distribution	86 (2.5)	-	82 (2.5)	-	
	Very Low	282 (27)	-	269 (27)	-	
	Low	485 (80)	-	464 (80)	-	
	Medium	542 (100)	-	518 (100)	-	
	High	606 (125)	-	579 (125)	-	
	Very High	664 (150)	-	635 (150)	-	
	Ultra High	766 (200)	-	733 (200)	-	
Electrical Specs - amps	Gas X	200-240V/50/60/1/3	15	10	15	10
Shipping Dimensions Approx. - in (mm)	Width	34.5 (876)		35.5 (902)		
	Depth	47.0 (1194)		54.0 (1372)		
	Height	83.0 (2108)		89.0 (2261)		
Net Weight - lb (kg)		770 (349)		910(413)		
Shipping Weight - lb (kg)		787 (357)		930 (422)		
Agency Approvals		CSA/UL/AGA/KTL/TISI		CSA/UL/AGA/KTL/TISI		