

primus®

GET AHEAD IN LAUNDRY+



DX13 | DX16 | DX24 Tumble Dryer



FAST DRYING



EASY OPERATION



SERVICE FRIENDLY

FEATURES & BENEFITS

Features

- Controls:
 - Dual Digital Control or OPL Micro
 - Coin operated version: XQ-Control
- Electrical or Gas heating
- Large door opening for easy loading and unloading Ø 57cm,DX13,16, Ø 68cm DX24)
- Galvanized drum
- Axial airflow
- Large lint filter

Options

- Stainless steel drum
- Coin operated version
- Reversing drum
- SafeTech™ Fire Suppression System
- Residual moisture control Sensodry+® (only with Full OPL Micro):
 - lower energy and utility costs
 - lower linen replacement costs

Specifications

TYPE		DX13	DX16	DX24
Capacity	kg(lb)	13(30)	16(35)	24(55)
Drum volume	l	270	350	490
Drum diameter	mm	Ø 673	Ø 726	Ø 838
AIRFLOW				
Airflow	l/s	240	280	330
DRYING AVERAGE				
Gas heating		267	349	485
Electric heating	g/min	258	340	371
MOTOR				
Fan	kW	0,4	0,4	0,4
Drive	kW	0,2	0,2	0,4
GAS HEATING				
Energy	kW	21,4	26,4	32,8
Energy		73	90	112
Electrical connection		1×100-120V/50-60Hz, 1-3×200-240V/50-60 Hz 3×440-480V/50-60Hz, 3×380-415V/50-60Hz		
Gas connection	NPT	½"	½"	½"
ELECTRICAL HEATING				
Energy	kW	21	24	27
Electrical connection		1×200-208V/50-60Hz, 3×200-208V/50-60Hz, 1x 230-240V/50-60Hz, 3x 230-240V/50-60Hz, 3x 380V/50-60Hz, 3x400-415V/50-60Hz, 3x 440V/50-60Hz, 3x 460-480V/50-60Hz		
STEAM HEATING				
Steam connection	NPT			3/4"
Steam pressure	bar			5.5 - 8.6
EXHAUST	Ø /m	150	200	200
DIMENSIONS				
Size H×W×D	mm	1625×710×1155	1625×800×1155	1700×875×1350
Net weight (E)	kg	150	160	200
Net weight (G,S)	kg	145	155	195
TRANSPORT DATA				
Packed (foil) H×W×D	mm	1720×760×1240	1720×840×1240	1790×900×1450
Gross weight (foil, E)	kg	160	170	220
Gross weight (foil,G,S)	kg	155	165	215
Packed (crate) H×W×D	mm	2210×880×1320	2210×950×1320	2210×1020×1520
Gross weight (crate, E)	mm	220	230	300
Gross weight (crate,G,S)	kg	214	220	295

