

primus®

GET AHEAD IN LAUNDRY+



DX34 Tumble Dryer

senso.dry+

SafeTech™



FAST DRYING



EASY OPERATION



LARGE DOOR OPENING

FEATURES & BENEFITS

Features

- Controls:
 - Dual Digital Control or OPL Micro
 - Coin operated version: XQ-Control
- Electrical or Gas heating
- Large door opening for easy loading and unloading (Ø 68cm)
- Galvanized drum
- Radial airflow
- Large lint filter

Options

- Stainless steel drum
- Coin operated version
- Reversing drum
- SafeTech™ Fire Suppression System
- Residual moisture control Sensodry+® (only with Full OPL Micro):
 - lower energy and utility costs
 - lower linen replacement costs

Specifications

TYPE	DX34	
Capacity	kg (lb)	34(75)
Drum volume	l	634
Drum diameter	mm	Ø940
AIRFLOW		
Airflow	l/s	380 (G 330)
DRYING AVERAGE		
Gas heating		571
Electric heating	g/min	521
MOTOR		
Fan	kW	0,4
Drive	kW	0,4
GAS HEATING		
Energy	kW	48,4
Energy	kBTU/h	165
Electrical connection		1×100-120V/50-60Hz, 1-3×200-240V/50-60 Hz 3×440-480V/50-60Hz, 3×380-415V/50-60Hz
Gas connection	NPT	½"
STEAM HEATING		
High pressure 6,9 bar	kw	39,24
	kBTU/h	133,9
Electrical connection		1×100-120V/50-60Hz, 1-3×200-240V/50-60 Hz 3×440-480V/50-60Hz, 3×380-415V/50-60Hz
Steam Connection	NPT	3/4"
Steam Pressure	bar	5.3 - 6.9
ELECTRICAL HEATING		
Energy	kW	27
Electrical Connection	NPT	1×200-208V/50-60Hz, 3×200-208V/50-60Hz, 1x 230-240V/50-60Hz, 3x 230-240V/50-60Hz, 3x 380V/50-60Hz, 3x400-415V/50-60Hz, 3x 440V/50-60Hz, 3x 460-480V/50-60Hz
EXHAUST	Ø /m	200
DIMENSIONS		
Size H×W×D	mm	1960×980×1350
Net weight (E ,G ,S)	kg	320, 310, 325
TRANSPORT DATA		
Packed (foil E ,G) H×W×D	mm	2060×1050×1420
Packed (foil S) H×W×D	mm	2120×1050×1420
Gross weight (foil,E ,G,S)	kg	340, 330, 350
Packed (crate) H×W×D	mm	2240×1170×1500
Gross weight (crate, E , G , S)	kg	410, 395, 415

