







FEATURES & BENEFITS

Features Rigid mounted, medium spin, 200G factor

- Stainless steel drum and tub, front panel and door, skin plate side panels
- Patented soap hopper
- Large door opening for easy loading & unloading

Options

- Liquid soap connection and pumps
- Anthracite cabinet
- Stainless steel cabinet (Vend)

Control

- XControl FLEX (Vend) fully programmable and customizable cycles 7" touch screen.
 - User-friendly screen with operating instructions built in as part of the control
 - Complete control content available in 34 languages
- XControl fully programmable control with 20 Pre-set programs and memory up to 99.
- XTronic Programmable control with 6 programs (+2 cycle modifiers and Imbalance detection)

SPECIFICATIONS

TYPE		PC20	PC30	PC40	PC60
INNERDRUM					
Capacity 1:09	kg (lb)	9(20)	13(29)	20(44)	28(62)
Capacity 1:10	kg (lb)	8(18)	12(26)	18(40)	25(56)
Volume	litres	79,3	119	178	255
Diameter	mm	533	610	668	762
G-FACTOR		200	200	200	200
HEATING					
Electricity	kW	5,4 -7,8	5,4 -7,8	10,8 -15,6	10,8 -15,6
Steam	bar				
Hot water	°C	66	66	66	66
Sound pressure level	dB (A)	< 61	< 65	< 65	< 651
Water valves connection	BSP	3/4"	3/4"	3/4"	3/4"
Rec. Water pressure	kPa	200-570	200-570	200-570	200-570
Flow amount with drain valve	l/min	40	40	40	70
Steam valve connection	BSP	-	-	1/2"	1/2"
Steam pressure	kPa	-	-	200-570	200-570
DIMENSIONS					
Size H×W×D	mm	1120×660×784	1171×737×896	1227×778×1073	1295×865×1135
Net weight	kg	150	200	245	308
TRANSPORT DATA					
Packed H×W×D	mm	1255×711×859	1303×800×973	1361×826×1105	1430×953×1191
Gross weight	kg	172	218	263	327

DIMENSIONS

PC20 660 784 1120 PC30 737 896 1171 PC40 778 1073 1227 PC60 865 1191 1295	D
	365
PC40 778 1073 1227 PC60 865 1191 1295	365
PC60 865 1191 1295	368
	379
width depth height	door bottom to floor

